

DCAM-API

Property List

For

C11440-10C

August 2013

HAMAMATSU

READ BEFORE USE

This document and the software sample codes are internal documents of Hamamatsu Photonics K.K. (HPK) and are disclosed upon request in order to enable the user to create an application using an HPK digital camera.

This document and the software sample codes are disclosed only for the purpose described above, and does not constitute a license, transfer, or any other entitlement for the owner.

All of the risks and results of using software depending on this document remains with the user.

This document may include technical inaccuracies or typographical errors. HPK does not guarantee any damages arising from such errors in this document.

HPK makes no commitment to update or keep current the information contained in this document.

All brand and product names are trademarks or registered trademarks of their respective owners.

HPK has copyright of this document with all rights reserved.

No part of this documentation may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form, or by any means, in any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise, without the prior written permission of HPK.

INTRODUCTION

This manual describes about properties which camera supports. To refer the detail explanation of each property, please see "Property Reference".

PROPERTY LIST AND VALUES

C11440-10C

C11440-10C Sensor mode			
DCAM_IDPROP_SENSORMODE	R/O	MODE	
DCAMPROP_SENSORMODE_AREA			
C11440-10C Trigger			
DCAM_IDPROP_TRIGGERSOURCE	R/W	MODE	
DCAMPROP_TRIGGERSOURCE_INTERNAL (DEFAULT)			
DCAMPROP_TRIGGERSOURCE_EXTERNAL			
DCAMPROP_TRIGGERSOURCE_SOFTWARE			
DCAM_IDPROP_TRIGGER_MODE	R/W	MODE	
DCAMPROP_TRIGGER_MODE_NORMAL (DEFAULT)			
DCAMPROP_TRIGGER_MODE_START			
DCAM_IDPROP_TRIGGERACTIVE	R/W	MODE	
DCAMPROP_TRIGGERACTIVE_EDGE (DEFAULT)			
DCAMPROP_TRIGGERACTIVE_LEVEL			
DCAMPROP_TRIGGERACTIVE_SYNCREADOUT			
DCAM_IDPROP_TRIGGER_GLOBALEXPOSURE	R/W	MODE	
DCAMPROP_TRIGGER_GLOBALEXPOSURE_DELAYED (DEFAULT)			
DCAMPROP_TRIGGER_GLOBALEXPOSURE_EMULATE			
DCAM_IDPROP_FIRSTTRIGGER_BEHAVIOR	R/W	MODE	
DCAMPROP_FIRSTTRIGGER_BEHAVIOR_STARTEXPOSURE			
DCAMPROP_FIRSTTRIGGER_BEHAVIOR_STARTREADOUT			
DCAM_IDPROP_TRIGGERPOLARITY	R/W	MODE	
DCAMPROP_TRIGGERPOLARITY_NEGATIVE (DEFAULT)			
DCAMPROP_TRIGGERPOLARITY_POSITIVE			
DCAM_IDPROP_TRIGGERDELAY	R/W	REAL, Second	
0 sec to 10 sec, default 0 sec			
DCAM_IDPROP_TRIGGERTIMES	R/W	LONG	
1 to 10000, default 1			
C11440-10C Binning and ROI			
DCAM_IDPROP_BINNING	R/W	MODE	
DCAMPROP_BINNING_1 (DEFAULT)			
DCAMPROP_BINNING_2			
DCAM_IDPROP_SUBARRAYHPOS	R/W	LONG	
0 to 1918, default 0			
DCAM_IDPROP_SUBARRAYHSIZE	R/W	LONG	
2 to 1920, default 1920			
DCAM_IDPROP_SUBARRAYVPOS	R/W	LONG	
0 to 1432, default 0			
DCAM_IDPROP_SUBARRAYVSIZE	R/W	LONG	
8 to 1440, default 1440			
DCAM_IDPROP_SUBARRAYMODE	R/W	MODE	
DCAMPROP_MODE_OFF(DEFAULT)			
DCAMPROP_MODE_ON			
C11440-10C Feature			
DCAM_IDPROP_EXPOSURETIME	R/W	REAL, Second	
21 usec to 10 sec, default 0.021991 sec			
DCAM_IDPROP_CONTRASTGAIN	R/W	LONG	
0 to 255, default 0			

C11440-10C ALU			
DCAM_IDPROP_CAPTUREMODE		R/W	MODE
	DCAMPROP_CAPTUREMODE_NORMAL (DEFAULT)		
	DCAMPROP_CAPTUREMODE_DARKCALIB		
	DCAMPROP_CAPTUREMODE_SHADINGCALIB		
DCAM_IDPROP_DEFECTCORRECT_MODE		R/W	MODE
	DCAMPROP_MODE_OFF		
	DCAMPROP_MODE_ON (DEFAULT)		
DCAM_IDPROP_SUBTRACT		R/W	MODE
	DCAMPROP_MODE_OFF (DEFAULT)		
	DCAMPROP_MODE_ON		
DCAM_IDPROP_SUBTRACTOFFSET		R/W	LONG
	0 to 10000, default 0		
DCAM_IDPROP_DARKCALIB_SAMPLES		R/W	LONG
	1 to 256, default 100		
DCAM_IDPROP_SUBTRACTIMAGEMEMORY		R/W	LONG
	1, 2, 3 or 4		
DCAM_IDPROP_STORESUBTRACTIMAGETOMEMORY		W/O	LONG
	1, 2, 3 or 4		
DCAM_IDPROP_SHADINGCORRECTION		R/W	MODE
	DCAMPROP_MODE_OFF (DEFAULT)		
	DCAMPROP_MODE_ON		
DCAM_IDPROP_SHADINGCALIB_SAMPLES		R/W	LONG
	1 to 256, default 100		
DCAM_IDPROP_SHADINGCALIBDATAMEMORY		R/W	LONG
	1, 2, 3 or 4		
DCAM_IDPROP_STORESHADINGCALIBDATATOMEMORY		W/O	LONG
	1, 2, 3 or 4		

C11440-10C Output Trigger			
DCAM_IDPROP_OUTPUTTRIGGER_POLARITY		R/W	MODE
	DCAMPROP_OUTPUTTRIGGER_POLARITY__NEGATIVE (DEFAULT)		
	DCAMPROP_OUTPUTTRIGGER_POLARITY__POSITIVE		
DCAM_IDPROP_OUTPUTTRIGGER_ACTIVE		R/O	MODE
	DCAMPROP_OUTPUTTRIGGER_ACTIVE_EDGE		
DCAM_IDPROP_OUTPUTTRIGGER_DELAY		R/W	REAL, Second
	0 sec to 10 sec, default 0 sec		
DCAM_IDPROP_OUTPUTTRIGGER_PERIOD		R/W	REAL, Second
	10 usec to 10 sec, default 22 usec		
DCAM_IDPROP_OUTPUTTRIGGER_KIND		R/W	MODE
	DCAMPROP_OUTPUTTRIGGER_KIND_LOW (DEFAULT)		
	DCAMPROP_OUTPUTTRIGGER_KIND_EXPOSURE		
	DCAMPROP_OUTPUTTRIGGER_KIND_PROGRAMABLE		
	DCAMPROP_OUTPUTTRIGGER_KIND_TRIGGERREADY		

C11440-10C Synchronous timing		
DCAM_IDPROP_TIMING_READOUTTIME	R/O	REAL, Second
return seconds how long takes to reading out a frame.		
DCAM_IDPROP_TIMING_CYCLICTRIGGERPERIOD	R/O	REAL, Second
return seconds which period cyclic trigger happens in.		
DCAM_IDPROP_TIMING_MINTRIGGERBLANKING	R/O	REAL, Second
return seconds required minimum trigger blanking.		
DCAM_IDPROP_TIMING_MINTRIGGERINTERVAL	R/O	REAL, Second
return seconds required minimum trigger interval.		
DCAM_IDPROP_TIMING_EXPOSURE	R/O	MODE
DCAMPROP_TIMING_EXPOSURE_ROLLING		
DCAM_IDPROP_INTERNALFRAMERATE	R/O	REAL, Second
0.1 to 45.454591		
DCAM_IDPROP_INTERNAL_FRAMEINTERVAL	R/O	REAL, Second
0.022 to 10.0		
DCAM_IDPROP_TIMING_GLOBALEXPOSUREDELAY	R/O	REAL, Second
0.0 to 0.022		
		See also EFFECTIVE flag
DCAM_IDPROP_TIMING_INVALIDEXPOSUREPERIOD	R/O	REAL, Second
0.0 to 0.021979		

C11440-10C System information		
DCAM_IDPROP_COLORTYPE	R/O	MODE
DCAMPROP_COLORTYPE BW		
DCAM_IDPROP_BITSPERCHANNEL	R/W	LONG
DCAMPROP_BITSPERCHANNEL_12		DCAM_DATATYPE_UINT16
DCAMPROP_BITSPERCHANNEL_14		DCAM_DATATYPE_UINT16
DCAM_IDPROP_IMAGE_WIDTH	R/O	LONG
return width pixel of current setting		
DCAM_IDPROP_IMAGE_HEIGHT	R/O	LONG
return height line of current setting		
DCAM_IDPROP_IMAGE_ROWBYTES	R/O	LONG
return horizontal rowbytes of current setting		
DCAM_IDPROP_IMAGE_FRAMEBYTES	R/O	LONG
return bytes per frame of current setting		
DCAM_IDPROP_IMAGE_TOPOFFSETBYTES	R/O	LONG
return 0		

© 2000,2013 Hamamatsu Photonics K.K.

HAMAMATSU

Homepage Address <http://www.hamamatsu.com>

HAMAMATSU PHOTONICS K.K., Systems Division

812 Joko-cho, Hamamatsu City, 431-3196, Japan, Telephone: (81)53-431-0124, Fax: (81)53-435-1574, E-mail: export@sys.hpj.co.jp

U.S.A. and Canada: Hamamatsu Photonic Systems, 360 Foothill Road, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1)908-231-1116, Fax: (1)908-231-0852, E-mail: usa@hamamatsu.com
Germany: Hamamatsu Photonics Deutschland GmbH, Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658, E-mail: info@hamamatsu.de
France: Hamamatsu Photonics France S.A.R.L., 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10, E-mail: info@hamamatsu.fr
United Kingdom: Hamamatsu Photonics UK Limited, Lough Point, 2 Gladbeck Way, Windmill Hill, Enfield, Middlesex EN2 7JA, United Kingdom, Telephone: (44)208-367-3560, Fax: (44)208-367-6384, E-mail: info@hamamatsu.co.uk
North Europe: Hamamatsu Photonics Norden AB, Smidesvagen 12, SE-171-41 Solna, Sweden, Telephone: (46)8-509-031-00, Fax: (46)8-509-031-01, E-mail: na@hamamatsu.se
Italy: Hamamatsu Photonics Italia S.R.L., Strada della Moia, 1/E/20020 Arese (Milano), Italy, Telephone: (39) 02-935 81 733, Fax: (39) 02-935 81 741, E-mail: info@hamamatsu.it